



CONVERGE



Server10 Lotto1 T630

Componente:
Server DELL PowerEdge T630 (1 CPU Intel® Xeon® ES-2640 v4, 32GB RDIMM, 2xHDD 300GB 10K RPM SAS 12GBps 2.5in)

PowerEdge T630

Category: Server

Quantity: 1



Base	PowerEdge T630 for Intel v4 CPUs	1	
Configurazione dello chassis	Chassis with up to 32, 2.5" Hard Drives, Tower Configuration	1	
Processore	Intel Xeon ES-2640 v4 2.4GHz 25M Cache 8.0GT/s QPI Turbo HT 10C/20T (90W) Max Mem 71.5MiB	1	
Processore aggiuntivo	No Additional Processor	0	
Processore Thermal Configuration	1 CPU up to 105W	1	
Tipo di configurazione memoria	Performance Optimized	1	
Total Memory in GB		32	
Tipo e velocità della memoria DIMM	2400MT/s RDIMMs	1	
Capacità di memoria	16GB RDIMM, 2400MT/s, Dual Rank, xL Data Width	2	
Sistema operativo preinstallato	CentOS 7.0	1	10L3-LINUX
Client Access Licenses	None		
Controller RAID	PERC H330 RAID Controller	1	
Dischi fisici	300GB 10K RPM SAS 12Gbps 2.5in Hot-plug Hard Drive	2	
	300GB 10K RPM SAS 12Gbps 2.5in Hot-plug Hard Drive, CusKit	0	10L1-HDD300GB-T
	1TB 7.2K RPM NL SAS 6Gbps 2.5in Hot-plug Hard Drive, 13G, CusKit	4	10L1-HDD1TB
Configurazione RAID HDD 300GB	C3 - RAID 1 for H330 (1 HDD)	1	
	Hot Spare for 300GB HDD	Yes	
Configurazione RAID HDD 1TB	C4 - RAID 3 for H330 (3-8 HDDs)	1	
	Hot Spare for 1TB HDD	Yes	
Impostazioni del BIOS per la gestione dell'alimentazione	Performance BIOS Setting	1	
Raffreddamento	Fresh Air Cooling	1	
Alimentazione	Dual, Hot-plug, Redundant Power Supply (1+1), 750W, Titanium, 200-240VAC	1	
Cavi di alimentazione	Italian Spare Power Cord 230V	2	
TPM Module	PowerEdge Server FIPS TPM 2.0	1	
Embedded Systems Management	iDRAC, Enterprise	1	
Adattatore di rete aggiuntivo	On-Board LOM 1GbE (Dual Port for Towers, Quad Port for Racks and Blades)	1	
	Broadcom 5720 DP 1Gb Network Interface Card	1	
Additional Card for PCIe Slot 1 (CPU 1)	None		
Additional Card for PCIe Slot 2 (CPU 1)	None		
Additional Card for PCIe Slot 3 (CPU 2)	None		
Additional Card for PCIe Slot 4 (CPU 2)	None		
Additional Card for PCIe Slot 5 (CPU 2)	None		
Additional Card for PCIe Slot 6 (CPU 2)	None		
Pannello frontale	Bezel	1	
Guida per rack	No Rack Rails, No Cable Management Arm, No Casters	1	
Unità ottica interna	No Internal Optical Drive, 2.5in Chassis	1	
Accessori per server	Redundant Fan Option	1	
	PowerEdge SFP+, 10GbE SR/SX, Optical Transceiver, LC Connector, for Intel and	0	
Aggiornamenti della garanzia	None		
Protezione dei dati - Keep Your Hard Drive	None		



PowerEdge T630 Conf.1 1 **Server**

1	Server Tower - 10L1-T630-U
-	-
-	-
-	-
-	-
-	-
-	-
-	-
-	-
4	OpzStorage1Tb - 10L1-HDD1TB
-	-
-	-
-	-
-	-
1	OpzOpenSource - 10L1-LINUX
-	-
-	-

Configurazione RAID

HDD 300 GB	C3 - RAID 1 for H330 (2 HDDs)
Hot spare HDD 300 GB	Yes

HDD 1000 GB	C4 - RAID 5 for H330 (3-8 HDDs)
Hot spare HDD 1000 GB	Yes

Note RAID

AREA RISERVATA AL FORNITORE

VERIFICA STAGING

VERIFICA INSTALLATORE